

Revision Date 01.01.2026
Date of first issue 09.01.2017

Material Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifiers

Product name Xylene
Product number W320314
Brand 3ASenrise
CAS number 1330-20-7

1.2 Details of the supplier of the safety data sheet

Company: Anhui Senrise Technology Co., Ltd.
Address: No.88 Weisan Road, High-Tech Industrial Development Zone, Anqing, Anhui
Post code: 246003
Tel: 400-005-6266
Fax: 0556-5555368
Email: service@3asenrise.com

1.3 Emergency telephone

Emergency telephone: 0556-5500208

1.4 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: For R&D use only. Not for pharmaceutical, household or other uses.

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Flammable liquids (Category 3), H226
Acute toxicity, Oral (Category 5), H303
Acute toxicity, Inhalation (Category 4), H332
Acute toxicity, Dermal (Category 4), H312
Skin corrosion/irritation (Category 2), H315
Serious eye damage/eye irritation (Category 2A), H319
Specific target organ toxicity - single exposure (Category 3), respiratory tract irritation, Narcotic effects, H335, H336
Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Central nervous system, Liver, Kidney, H373
Aspiration hazard (Category 1), H304
Short-term (acute) aquatic hazard (Category 2), H401
Long-term (chronic) aquatic hazard (Category 3), H412

2.2 GHS label elements, including precautionary statements

Pictogram



Signal word: Danger

Hazard statement(s)

H226 Flammable liquid and vapour.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P304+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P331 Do NOT induce vomiting.

P332+P313 IF SKIN irritation occurs: Get medical advice/attention.

P337+P313 IF eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Physical and chemical hazards

H226 Flammable liquid and vapour.

2.4 Health hazards

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

2.5 Environmental hazards Code

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

2.6 Other hazards

No data available

3 COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture: Substance

3.1 Substance

Name	Xylene
Formula	C ₈ H ₁₀
Molecular Weight	106.17
CAS	1330-20-7
Concentration	99%, Extra Dry, Water ≤ 50 ppm (by K.F.), EnergySeal

4 FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with

water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

5 FIREFIGHTING MEASURES

5.1 Extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

5.2 Special hazards arising from the substance or mixture

Carbon oxides Combustible. Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated temperatures. Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

6.4 Reference to other section

For disposal see section 13.

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Long term storage: RT

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

No data available.

8.2 Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses.

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product.

Body protection

Flame retardant antistatic protective clothing.

Respiratory protection

If the exposure limits are exceeded, irritation or other symptoms are experienced, use a full-face respirator.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance	Colorless liquid
b) Odor	No data available
c) pH	No data available
d) Melting point/freezing point	No data available
e) Initial boiling point and boiling range	137 – 140 ° C at 1,013 hPa
f) Upper/lower flammability or explosive limits	Upper explosion limit: 7.0 %(V) Lower explosion limit: 1.1 %(V)
g) Flash point	25 ° C – closed cup
h) Evaporation rate	No data available
i) Vapor pressure	23.99 hPa at 37.70 ° C
j) Vapor density	No data available
k) Density	0.865 g/cm ³ at 20 ° C
l) Water solubility	0.1705 g/l at 25 ° C – partly soluble
m) Partition coefficient: n-octanol/water	No data available
n) Autoignition temperature	463 ° C at 1,013 hPa
o) Decomposition temperature	No data available
p) Flammability	No data available

10 STABILITY AND REACTIVITY

10.1 Chemical stability

No data available.

10.2 Conditions to avoid

No data available.

10.3 Incompatible materials

No data available

10.4 Hazardous decomposition products

In the event of fire: see section 5.

11 TOXICOLOGICAL INFORMATION

11.1 Acute toxicity

LD₅₀ Oral

– Rat – male – 3,523 mg/kg

LC₅₀ Inhalation

– Rat – male – 4 h – 29.09 mg/l – vapor

LD₅₀ Dermal

– Rabbit – > 1,700 mg/kg

11.2 Skin corrosion/irritation

Skin – Rabbit Result: Moderate skin irritation – 24 h Remarks: Drying-out effect resulting in rough and chapped skin.

11.3 Serious eye damage/eye irritation

Eyes – Rabbit Result: Causes serious eye irritation. – 24 h

11.4 Respiratory or skin sensitization

Local lymph node assay (LLNA) – Mouse Result: negative

11.5 Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration. Test system: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Result: negative Remarks: (National Toxicology Program) Test Type: Ames test Test syste

11.6 Carcinogenicity

No data available

11.7 Reproductive toxicity

No data available

11.8 Specific target organ toxicity - single exposure

May cause respiratory irritation. - Respiratory system

11.9 Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Central nervous system, Liver, Kidney

11.10 Aspiration hazard

no data available.

11.11 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 90 d - NOAEL (No observed adverse effect level) - 150 mg/kg - LOAEL (Lowest observed adverse effect level) - 150 mg/kg RTECS: ZE2100000 Blurred vision, Incoordination., Headache, Nausea, Vomiting, Dizziness, Weakness, anemia, Prolonged or repeated exposure to skin causes defatting and dermatitis. To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. After absorption: Systemic effects: Headache somnolence Dizziness agitation, spasms narcosis inebriation Effect potentiated by: ethanol Other dangerous properties can not be excluded. Handle in accordance with good industrial hygiene and safety practice.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish:

static test LC50 - *Oncorhynchus mykiss* (rainbow trout) - 2.60 mg/l - 96 h

Toxicity to daphnia and other aquatic:

No data available

Toxicity to algae:

static test EC50 - *Pseudokirchneriella subcapitata* - 4.36 mg/l - 73 h

Toxicity to bacteria:

No data available

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d Result: 94 % - Readily biodegradable.

12.3 Bioaccumulative potential

Bioaccumulation *Oncorhynchus mykiss* (rainbow trout) - 56 d at 10 ° C - 1.3 mg/l(Xylene)

Bioconcentration factor (BCF): 7.4 - 18.5

12.4 Mobility in soil

No data available

12.5 Other adverse effects

No data available

13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Observe all federal, state and local regulations when disposing of the substance.

Contaminated packaging

Disposal must be made according to official regulations.

14 TRANSPORT INFORMATION

14.1 UN number

ADR/RID: 1307 IMDG: 1307 IATA: 1307

14.2 UN proper shipping name

ADR/RID: XYLENES

IMDG: XYLENES

IATA-DGR: XYLENES

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

14.4 Packaging group

ADR/RID: III IMDG: III IATA: III

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Applicable regulations

Regulations on the Control over Safety of Dangerous Chemicals.

This product is included in the list of dangerous chemicals.

Please pay attention to waste disposal and meet the requirements of local regulations.

16. OTHER INFORMATION

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Dangerous Goods

IATA: International Air Transport Association

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

CAS: Chemical Abstracts Service (division of the American Chemical Society)

Further information

The above safety technical information is for reference only, because many physical and chemical properties are not entirely clear. Please consult information carefully before use and use after confirmation.

Anhui Senrise Technology Co., Ltd. shall not be held liable for any damage resulting from handling or from contact with the above product. More terms of use, see invoice information for details.

Tel: +86 -400-005-6266 Fax: +86 -0556-5555368 E-mail: Service@3asenrise.com

Add: No.88 Weisan Road, High-Tech Industrial Development Zone, Anqing, Anhui